



IP67 junction box and connector have a high degree of waterproof, effectively resist the harsh environment



Excellent Anti-PID performance guarantee limited power degradation for mass production




Excellent anti-microcracking performance with more balanced interior stress




10 years limited product warranty, 25 years linear power warranty

Engineering Drawings



Electrical Performance & Temperature Dependence



Web: www.ntsolartech.com

The company reserves the final right for explanation on any of the information presented hereby.

NT160-M10

Mechanical Specifications

Cell Type	Mono 182mm*121.3mm
Dimensions	1030*770*30mm
No. of cells	32 (4*8)
Front Glass	3.2mm, Anti-Reflection Coating, High Transmission
Frame	Anodized Aluminium Alloy
Junction Box	IP67 Rated
Output Cables	TUV 1x4.0mm ² , 90mm Length or Customized Length
Weight	9.0kg

Packaging Configuration

1780pcs/ 40'HQ Container

Electrical Specifications At STC

Max. Power (Pmax)	160W
Max. Power Voltage (Vmp)	19.1V
Max. Power Current (Imp)	8.37A
Open-circuit Voltage (Voc)	22.92V
Short-circuit Current (Isc)	8.87A
Module Efficiency (%)	20.2%
Power Tolerance	0~+5W
Maximum system voltage	1500VDC
Maximum series fuse rating	15A
Temperature Coefficients of Pmax	-0.35%/C
Temperature Coefficients of Voc	-0.29%/C
Temperature Coefficients of Isc	0.048%/C

STC Irradiance 1000W/m², Cell Temperature 25°C, AM=1.5

Operating Conditions

Maximum System Voltage	1000V/1500V DC(IEC)
Operating Temperature	-40°C~+85C
Maximum Series Fuse	15A
Maximum Static Load,Front	5400Pa
Maximum Static Load,Back	2400Pa
Safety Class	Class II